

SAFETY DATA SHEET

Castleflex Interlocking Rubber Tiles

PRODUCT AND COMPANY IDENTIFICATION

Product type: Rubber Tiles
Trade Name: "Castleflex"

Manufacturer: Castle Composites Limited

Units 1-5, Nisbet Way

Ravenstruther Lanark, ML11 7SF

Phone No.: 01555 870003 Fax No.: 01555 870040

Packing Information

Stacked on wooden pallets with shrink wrap. Interlocking pins contained within a bag at the top of each pallet

Product Information

Composition: Recycled Rubber Granulate bound using poly urethane binding agent and colouring agents.

Size: 500x500x30mm

Colours: Black, Red, Green Charcoal, Chocolate, Sand, Golden. Due to the recycled nature of the product these colours are not colour fast and variation in colour may occur.

Density: 800kg/m3

Fire Resistance: Broof(t1) as per EN 13501-5

Test Passed to Rating Efl as per EN 13501-1 (Product capable of resisting small flames)

Smoke Resistance: S2 and per EN 13501-1

Size Tolerance: Width 2%, Thickness 2%

Carbon Leaching: Carbon Black is a colouring agent

Guarantee: 5 Years for wear resistance, provided the product is used for roof terraces or balconies. The

guarantee does not apply to colour.

Recycling: 100% Recyclable

Insulation Value: Rd 0,15 EN13165, U 3,13 EN6946

Water Permeability: 565mm Per Hour EN12616